VEHICLE INSPECTION REPORT

MAKE:		MODEL											
ENGINE No.							VI	N:					
ADR 2/00	DOOR LATCHES AND HINGES.	<u> </u>			1								
CLAUSE NO	FEATURI	FEATURE						Compliance				NCI NO	
2.1.1	Two latch positions?							y [] N		NA C		
2.1.1.1/2	Longitudinal and transverse restraints?							γ [] N		NA C]	
2.1.3	Locks on all side doors and operating me	echar	nism in	the inte	rior	?		γ [] N		NA C		
2.1.3.1	Do front door locks prevent their openir	ng fro	m outs	ide?				y [I N		NA C		
2.1.3.2	Rear Door Locks MA only Do the rear door locks prevent their opening from inside and outside? or					ν [□ N		NA 🗖				
	Rear door locks prevent opening from o engagement of 'Child Safety Locks?'	utsid	e and, i	nside b	У			y [] N		NA C		
2.4	If 'E' marked R11, Approval No.									#			
ADR 3/02	- SEATS AND SEAT ANCHORAGES												
CLAUSE NO	FEATURI	Ξ							Co	mpl	iance		NCI NO
5.8.1	Self-locking restraining device and relead hinged seats or seat backs?	se co	ntrol p	rovided	on a	III		y [] N		NA C		
5.8.2	Where seat must hinge for access, is release control readily accessible to the occupant of the seat and one immediately behind?			y [J N		NA C						
5.8.6	Where 'SEATS' are mounted on hinged of latching?	engin	e covei	s, is cov	er se	elf		y [] N		NA C		
5.9.1	Are rear upper parts of seat and head re another seat?	straii	nt pado	led if in	fron	t of		y [] N		NA C		
7	If 'E' marked R17, Approval No.									#			
ADR 4/02	and ADR 4/03 – SEATBELTS												
CLAUSE NO	FEATURI	=							Co	mpl	iance		NCI NO
	Are new seat belts fitted?, if 'NO'							γ [] N		NA 🗖		
	Do seat belts appear in an acceptable co	nditi	on as p	er guid	eline	s?		γ [] N		NA C		
4/02, 5.3.1	Retractor lap sash seat belts on all outbo folding 3 rd row cargo area ADR 5/04 CI 5	.3(2).		positio	ns? e	excep	ot	y [] N		NA C	1	
	(Note outboard positions without retrac	tors)											
Notes:													

CLAUSE NO		Compliance	NCI NO		
4/02, 5.2	Lap belts, at least, for all of	y \square N \square NA \square			
	For swivelling seats is a sea which the seat may be lock Is there a durable label wit	red? If NO,	·	y N NA NA NA	
	BE USED IN THE (FORWARI POSITION WHILST THE VEH swivelling seat and visible t Is a facsimile of the label p	Y			
4/02, 5.7	For any two seating position, identify:	(1)	(2)		
	(1) location				
	(2) mfr name/trade mark #			y	
	(3) date of manufacture M/Y(not required if ECE)			Y N NA NA NA	
	(4) identification code #			y \square N \square NA \square	
	(5) AS2596 Lic no			Y N N NA	
	Buckle Identification code if different to Lap/Sash			Y N NA NA	
4/02,20.1	If `E' marked R16, Approval No			#	
4/02, 4/03, 5.3.1.1	Driver's seatbelt only incor	porate an ELR?		Y N NA NA	
4/02, 4/03, 5.3.1.2	All other outboard seatbel	ts incorporate an ELR and	d/or an ALALR?	Y N N NA	
4/02,4/03 6.1.1	For drivers seating position '95 th Percentile Adult Male position, and a '5 th Percent rearmost driving position.	with the seat in the fore ile Adult Female', with t	emost driving he seat in the	Y N N NA N	
4/02,4/03. 6.1.2	For all other seating position 95 th Percentile Adult Male' and a '50 th Percentile 6 Year riding position.	with the seat in the fore	emost riding position,	y D N D NA D	
4/02,4/03, 5.4	Removal of seatbelt assem without tools prevented?	bly or separation of fund	tional components	y	
4/02,4/03 5.8.1	Are all buckles of a quick-re	elease design?		y □ N □ NA □	
4/02,4/03 5.8.1	Are release instructions pri the release coloured red or		of the buckle and/or	y □ N □ NA □	
Notes:					

VEHICLE INSPECTION REPORT

CLAUSE NO	FEATURE	Compliance	NCI NO
4/02,4/03, 5.9	Instructions specified for use of seat belt assembly in the vehicle handbook or otherwise supplied as per ADR?	Y	
4/02, 4/03, 6.3.2	Any free end of strap of a seatbelt, (1) Prevented from passing through an adjuster? (2) Have at least 25mm available grip when fully extended? For 'Outboard Seating Positions' adjacent to a door, (3) Restrained against another strap?	Y	
4/02,4/03, 7.4	Buckle component of the retracting strap accessible?	Y N N NA	
4/02,4/03, 7.5	Buckle component of the non-retracting part of seatbelt assembly (for individual front seats), supported by rigid member and pivots no more than 50mm vertically?	Y N NA NA	
4/02,4/03, 7.6	Positive feature to restrain outboard buckles?	Y N N NA	
ADR 5/03	and 5/04- ANCHORAGES FOR SEATBELTS		_
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
5.2.1	Seat belt anchorages for all seating positions?	y \square N \square NA \square	
5.5.5	No upper torso anchorage for any side facing seat?	y N N NA	
7.1.1	Lap anchor points on opposite sides of 'Seating Reference Plane'; minimum separation at least 165 mm?	Y N N NA N	
13	If 'E' marked R14, Approval No	#	
ADR 8/00	and 8/01 - SAFETY GLAZING MATERIAL		
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
8/00, 8.1.4 8/01, 5.3	Is transparent material other than glass used in the vehicle? If YES, note the location and markings.	Y	
8/00, 8.2.1 8/01, 6.1	All glazing suitably marked?	Y N N NA	
8/00, 8.2.3	If toughened windscreen, modified zone indicated?	y \square N \square NA \square	
8/01, 5.4	Windscreen glass marked as being laminated?	y	
Notes:			

VEHICLE INSPECTION REPORT

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
8/00, 8.4 8/01, 8.1	Glazing standard and approval No. (1) Windscreen? (2) Driver's side Window? (3) Rear screen?	#	
ADR 10/0	1 - STEERING COLUMN		
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
10.2.2	Steering column appears to have collapsible element?	y \square N \square NA \square	
10.4	If 'E' marked' R12, Approval No	#	
ADR 11/0	D – INTERNAL SUN VISORS		_1
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
11.1.1	IF SUN VISORS FITTED ARE THEY PADDED?	y N NA NA	
11.2.1	DO MOUNTINGS HAVE ANY EDGE WITH A RADIUS LESS THAN 3MM?	y N N NA	
11.2.2	IF MIRROR FITTED, THICKNESS OF ENERGY ABSORBING MATERIAL AROUND EDGE OF MIRROR, AT LEAST 1.5MM?	Y N N NA	
	IF 'E' MARKED R21, APPROVAL NO:	#	
			1

Notes:		
	•••••	

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

ADR 13/00 - INSTALLATION OF LIGHTS & LIGHT SIGNALLING DEVICES

NOTE These inspection items are based on the latest issue of ADR 13/00. Vehicles may be certified to previous versions of ADR 13/00 that were in force at the time the vehicle was originally built.

- (1) If any item in column 1 is 'E' Marked note marking in Column 2.
- (2) Audit all items for each of Columns 3 to 9 inclusive, Circle non-compliances, otherwise tick.
- (3) Indicate compliance status for table at end in space provided.

			FEATURES					
(1) FEATURE	(2) If 'E' Marked	Heig	ght (#)	(5) APART	(6) EDGE	(7) G	(8) C	(9) R
(CLAUSE NO)	Approval NO	(3) MAX	(4) MIN	(#)	(#)	(*)	(*)	(*)
Main beam (*)					(*)			
(CI A.6.1.)&(A.6.1.4)					Dipped beam	Dip		Dip
Dipped beam (*)			(*)					
(Cl A.6.2.)		1200	500		500	Main		Main
Front fog lamp (+)		800 and						Main
(Cl A.6.3)		<dip. beam<="" td=""><td>250</td><td></td><td>440</td><td>%f</td><td></td><td>Swiv</td></dip.>	250		440	%f		Swiv
Reversing lamp (*)								
(Cl A.6.4)		1200	250			%r		
Direction indicator Front		1500/	300(MA only)	400(MA only)				
(Cl A.6.5)& (A.6.5.4.2 (*)	4	>2100	350	600	400	%f		Park
Direction indicator Rear		1500/		400(MA only)				
(Cl A.6.5)& (A.6.5.4. (*)		>2100	350	600	400	%r		Park
Direction indicator Side		1500/						
Cl A.6.5.)& (A.6.5.4.2 (*)		>2300	350			%		Park
Stop lamp (Cl A.6.7)& (A.6.7.1.)		1500/			400			
(*)		>2100	350			%r		Park
Cornering Lamp (*) (Cl 7.4.1		<dip. beam<="" td=""><td></td><td></td><td></td><td></td><td></td><td></td></dip.>						
	<u>I</u>	1	FEATURES					

Notes:	 	 	
•••••	 	 	• • • • • • • • • • • • • • • • • • • •

(1) FEATURE	(2)If 'E' Marked	Hei	ght (#)	(5) APART	(6) EDGE	(7) G	(8) C	(9) R
(CLAUSE NO)	Approval NO	(3) MAX	(4) MIN	(#)	(#)	(*)	(*)	(*)
Centre High mounted stop lamp (CI A.6.7) ECE R48 approved only			<150 below bottom edge of rear screen or > 850 above ground					
Rear registration plate lamp (*)							Rpos	%r
(Cl A.6.8)								
Fr. Position lamp		1500/						
(Cl A.6.9) (*)		>2100	350		400	%f	SMar	%f
Rr. position lamp		1500/	350		400			
(Cl A.6.10.) (*)		>2100				%r	Reg	%r
Rear fog lamp(+) (Cl A.6.11), (A.6.11.4.) & (A.6.11.9)		1000	250	≥100 FROM STOP		%r		RPos Park
Parking Lamp (+)		1500/						
(Cl A.6.12)		>2100	350		400	%		%
Reflex reflector Rear (*) (Cl A.6.14)		900 >1500	250		400	%r	C/ Parts	
(Non-triangular) Front (+) (Cl A.6.16.)		900 ≽ 1500	250	600/ <400 (A.6.16.4.1)	400	FPos	C/ Parts	
Side (+)		900				%		
(Cl A.6.17)		>1500	250					
Side marker lamps (+) (Cl.A.6.18) or (Cl 7.2)		1500/ >2100	250(cl A.6.18) 600 (Cl 7.2.4.2)				Fpos	
Day time running lamp (+)				600/ <400				

Notes:		

VEHICLE INSPECTION REPORT

(1) FEATURE	((2)If 'E' Marked	Heig	ght (#)	(5) APART	(6) EDGE	(7) G	(8) C	(9) R
(CLAUSE NO	O)	Approval NO	(3) MAX	(4) MIN	(#)		(#)	(*)	(*)	(*)
(CIA.6.19))		1500	250	(A.6.19.4.1)	4	100	%f	%f	Indic
Cornering lan Cl A.6.20			900 and <dip. Beam</dip. 	and <dip.< td=""><td></td><td></td><td></td></dip.<>						
lowest (Min)p surface. APART - Distar edges of illum EDGE - Maxim edge of vehicl All dimensions Column (7) to which may be (C), or reciprodes = Permitted %f = Permitted lamp.	- To hipoints of nice be ninating num disterto illustration of the control of the	ghest (Max) and on illuminating tween innermost g surface. stance from outer uminating surface.	Beam. Dip = Pe Main = Fpos = F lamps. C/Part = Lamp. Park = F Lamps. FPos = F Lamps. RPos = F Lamps. Reg = P Plate Indic = F	Dip = Permitted with Dipped Beam. Main = Permitted with Main Beam. Fpos = Permitted with Front Position lamps. C/Part = May have common parts with a Lamp. Park = Permitted with Park Lamps. Smar = Permitted with Side Marker Lamps. FPos = Permitted with Front Position Lamps. RPos = Permitted with Rear Position Lamps. Reg = Permitted with Rear Registration Plate Lamp. Indic = Not permitted with Indicator Lamps. Swiv = Not permitted to swivel					IANCE NA	NCI NO
CLAUSE NO			FEAT	URE			СО	MPLI	ANCE	NCI No
A.2.13	VISIBILITY Are apparent surfaces of all lamps unobstructed by any parts of the vehicle (including options eg. bull-bar)? No lamps damaged , all lens not faded or cracked?					Y 1				
Notes:										

CLAUSE NO	FEATURE	COMPLIANCE	NCI No
_	CENTERAL		INO
A.5	GENERAL	y \square N \square NA \square	
A.5.5.1	Are all lamps constituting a pair symmetrical? (Except reverse and rear fog lamps)	Y LJ N LJ NA LJ	
A.5.10	No red light visible from the front and no white light (except reversing light) visible from the rear of the vehicle?	y	
A.5.11	Can all front and rear position lamps, the rear registration plate lamp, and the side marker lamps (if fitted) be only switched on and off together?	y	
A.5.12	Is it not possible to switch on the main-beam, dipped-beam and front and rear fog lamps with out first switching on the lamps referred to in clause A.5.11?	y	
A.5.14.1	Are no lamps (other than driving, dipped beam or front fog lamps) concealed?	Y N N NA	
A.5.14.2	Is it possible to move a concealed lighting device into the position of use, without the aid of tools, in the event of a defect?	Y N N NA	
A.6.1	MAIN-BEAM HEADLAMPS		
A.6.1.6	If main-beam headlamps swivel with steering, do they function as main-beam only?	Y N N NA	
A.6.1.7.1	Are all main beams switched off when changing over from main beam to dipped beam?	y	
A.6.1.8	Circuit closed tell-tale fitted and operating ?	y 🔲 n 🗎 na 🔲	
	DIPPED – BEAM HEADLAMPS	y \square N \square NA \square	
A.6.2	Control within easy reach of driver?	y \square \square \square \square \square	
A.6.2.8	Is a tell-tale fitted?	T = N = NA =	
A.C. 2.7	(1) If bend lighting is fitted is the additional light source located in the dipped-beam headlamps or in a lamp (except Main-beam) grouped or reciprocally incorporated with the respective dipped-beam headlamp?	y	
A.6.2.7	(2) If dipped-beam headlamps are switched ON or OFF automatically is it possible to switch these dipped-beam headlamps ON and OFF manually?	y 🗆 n 🗆 na 🗆	
A.6.2.8	Where the whole beam or the kink of the elbow of the cut-off is moved to produce bend lighting is a flashing warning light provide in the event of a malfunction of the displacement of the kink of the elbow of the cut-off?	y	
Notes:			

......

CLAUSE NO	FEATURE	COMPLIANCE	NCI No
	DIPPED – BEAM HEADLAMPS WITH GAS-DISCHARGE LAMPS		
A 6.2.9	Gas-discharge headlamps fitted with cleaning device(s) and automatic levelling device?	Y N N NA	
A.6.2.7	Do dipped-beam headlamps remain switched on during main-beam operation?.	y	
	FRONT FOG LAMP (OPTIONAL)		
A.6.3.7	Can the front fog lamps be switched on and off independently of the Main beam & dipped beam Headlamp?	Y N N NA N	
A.6.3.8	An independent non-flashing Circuit-closed tell-tale fitted? (Mandatory from 21/7/00)	Y N N NA	
	REVERSING LAMPS		
A.6.4.7.1	Is the lamp always lit when reverse gear engaged? and	Y N N NA NA NA	
7.101.17.12	The device controlling starting and stopping engine is in a position where engine can operate?	y N NA NA NA	
A.6.5.7	DIRECTION INDICATOR LAMPS	y \square \square \square \square \square	
A.0.3.7	Independent switch and flash in phase?	Y LIN LINA LI	
A.6.5.8	(1) Is a visible and/or audible 'operational tell-tale' fitted?	y \square N \square NA \square	
A.6.5.8	(2) Tell-tale behaviour on turn signal malfunction?		
A.6.5.9	(A) - Marked frequency change (B) - Continuously on or (C) – Continuously off (Indicate A, B, C,)		
	(1) Lights up in 1 sec. And flashes 60 to 120 per min?	y \square N \square NA \square	
	(2) Extinguishes within one and one half seconds?	y \square N \square NA \square	
	(3) If one lamp fails (other than due to a short-circuit)do other lamps flash when actuated?	Y N N NA	
	HAZARD WARNING LAMP	y \square N \square NA \square	
A.6.6.1	All direction indicator lamps flash in phase?	Y LI N LI NA LI	
A.6.6.7	Independent switch?	y \square N \square NA \square	
A.6.6.8	Flashing 'circuit closed tell-tale' fitted?	y \square N \square NA \square	
A.6.6.9	Can Hazard Warning be activated with engine off?	y \square N \square NA \square	
7.4.7.1	CORNERING LAMPS (Optional Certified to ADR 13/00 CI 7.4)	y	
7.4.7.1	Lighted continuously with corresponding Direction Indicator?		
7.4.7.2	Lighted only when Headlamp switch is 'ON'?	y \square N \square NA \square	
Notes:			

CLAUSE NO	FEATURE	COMPLIANCE	NCI No
	STOP LAMPS		
A.6.7.7	Lighted with service brake application with ignition ON?	y	
A.6.7.8	If fitted, is 'operating tell-tale' non-flashing type?	y \square N \square NA \square	
	CENTRE HIGH MOUNTED STOP LAMP (Certified to ECE R 48)		
A.6.7.2	Fitted on vehicle medium longitudinal plane, or offset if located on one or two movable parts of the vehicle (e.g. doors)?	y 🗆 n 🗆 na 🗖	
	If offset are '1' or '2' lamps fitted (Please circle)		
A.6.8.2	REAR REGISTRATION PLATE LAMP	y \square N \square NA \square	
71.0.0.2	Illuminates the registration plate area?		
	FRONT POSITION LAMPS		
A C O O	Instrument light as tell-tale?	y \square N \square NA \square	
A.6.9.8	If No, is a non-flashing tell-tale fitted?	y O N O NA O	
	Colour WHITE , or AMBER if combined with Side Marker Lamp (Please Circle)	Y LI N LI NA LI	
	REAR POSITION LAMPS		
A.6.10.8	Common 'circuit-closed tell-tale' with front position lamps?	Y N NA NA	
	REAR FOG LAMPS (OPTIONAL)		
A. 6.11.4.1	If only one rear fog lamp is fitted, is it mounted on the centre line or to the right hand side?	Y N N NA	
A.6.11.9	Distance between illuminated surface of the rear fog lamp and each stop lamp greater than 100mm?	y	
A.6.11.7.1	Can rear fog lamp operate only when dipped beam, main beam lamps or the front fog lamp is on?	y 🔲 N 🔲 NA 🔲	
A.6.11.7.4	When rear fog lamp is switched 'ON', does it remain 'ON' when switching from dipped to main beam?	y	
A.6.11.7.2	Can rear fog lamp be extinguished independently of any other lamps?	y \square N \square NA \square	
A.6.11.7.3. 1	Rear fog lamps are switched off and remain off (until deliberately switched on again) when the position lamps are switched 'OFF'? or	y	
or	Audible warning provided with ignition key removed, drivers door open		
A.6.11.7.3. 2	and the rear fog lamp switch 'ON'?	Y N NA NA NA	
A.6.11.8	Independent, non-flashing, circuit closed tell-tale fitted and operational?	y	
Notes:			

CLAUSE NO	FEATURE	COMPLIANCE	NCI No
A.6.12.7	PARKING LAMP (OPTIONAL) (1) Switch to permit parking lamps on the same side to be lit independently of any other lamps?	y	
	(2) Able to operate with the ignition switch in 'OFF' position?	Y N N NA N	
A.6.12.8	If fitted, impossible to confuse tell-tale with that for the front and rear position lamps?	Y N N NA	
A.6.18.8	SIDE MARKER LAMPS (CERTIFIED TO ECE R48) OPTIONAL (MANDATORY for vehicle exceeding 6m in length) If Optional tell-tale fitted, is it the same as that for the front and rear position (side) lamps?	y	
A.6.18.4.3	If less than 6m in length, lamps fitted to front 3 rd of vehicle and/or rear 3 rd of vehicle?	y	
A6. 18.4.3	If more than 6m in length, at least one lamp fitted to the middle 3 rd , the distance between two adjacent lamps not more than 3m, and the foremost lamp within 3m of the front, & the rearmost lamp within 1m of the rear?	y	
A.6.18.7	If 'Amber' and flash, do they flash in phase with indicators?	y \square N \square NA \square	
A.6.19.7	DAYTIME RUNNING LAMP (OPTIONAL) If fitted, switch off automatically when headlamps are switched 'ON'?	y	
A.6.20	CORNERING LAMPS (Certified to ECE R 48/02 OPTIONAL)		
	(1) Are corning lamps so connected that they cannot be activated unless the main-beam headlamp or the dipped-beam headlamps are switched ON at the same time?.	y	
A.6.20.7	(2)Are lamps only switched ON automatically when the direction indicator on the same side of the vehicle are switched ON and/or the steering angle is changed from the straight-ahead positiontowards the same side of the vehicle?	Y	
	(3) Are cornering lamps switched OFF automatically when the direction indicator is switched OFF and/or the steering angle has returned in the straight-ahead position?.	Y	
A.6.20.9	Cornering lamps are not activated at vehicle speeds above 40km/h?	y 🔲 n 🔲 na 🔲	
			•

Notes:	

VEHICLE INSPECTION REPORT

ADR 14/0	1, 14/02 – REA	AR VISION MIRROR			
CLAUSE NO		FEATURE		COMPLIANCE	NCI NO
14/01 , 14.2.0	Reflective surface	ces of all mirrors flat?		Y N N NA	
14/02 ,14.	Reflective surface	ce of the internal mirror 'Flat' or '	Convex'? (Circle one)	y \square N \square NA \square	
2.1 14.2.3.1.1	If Internal mirro	r 'Convex', is it 'E Marked'?		y \square N \square NA \square	
1112131111	Driver's externa	l mirror fitted? , is it 'Flat' or 'Con	vex'?. (Circle one)	y \square N \square NA \square	
	If Driver's extern	nal mirror 'Convex' is it 'E Marked	'?	y O N O NA O	
	If LHS external mirror fitted, is it 'Flat' or 'Convex'? (Circle one).				
				Y O N O NA O	
14.2.3.1.1	RHS external mirror adjustable from the drivers seating position?			y 🔲 N 🔲 NA 🔲	
14.2.3.1.1	RHS external mirror not obscured by the unwiped portion of the windscreen?			y 🗆 n 🗆 na 🗆	
	If `E' marked	Internal	External		
14.6	R46, Approval NO.			#	
ADR 18/0	1 & 18/02 - IN	STRUMENTATION			
CLAUSE NO		FEATURE		COMPLIANCE	NCI NO
18/01,	MA Category O	nly.			
18/02,		n driver's side and all visual indica	tors readily visible by	y \square n \square na \square	
18.3	the driver?		2		
18/01,18/ 02, 18.4.2	Speed indicating	g element colour and background	contrast?	y 🗆 n 🗆 na 🗆	

18/01,	MA Category Only.		
18/02,	Speedometer on driver's side and all visual indicators readily visible by	y 🔲 n 🔲 na 🔲	
18.3	the driver?		
18/01,18/	Speed indicating element colour and background contrast?		
02,		y 🔲 n 🔲 na 🔲	
18.4.2			
18/01,	For All Vehicle Categories.	y \square N \square NA \square	
18/02.	Vehicle speed indicated in Km/h only?		
18.5.1.1.1	If 'NO' is Major Scale Km/h?	Y N N NA	
18/01,18/	Speedometer readily visible to the driver?		
02.		y \square n \square na \square	
18.5.1.2			
18/01,18/	Odometer. Distance travelled indicated in a least 1Km units least from 1		
02.	to 999 999 Km (18/01) or 600 000 Km (18/02)	y \square n \square na \square	
18.5.2.1.1			

Notes:	

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

ADR 18/03 - INSTRUMENTATION (From 01-JULY-2006 for ALL NEW MODELS)

CLAUSE NO	FEATURE		COMPLIANCE	NCI NO
5.1	Vehicle speed indicated in km/h only? If NO Is the mp/h scale the secondary scale?		Y	
A.5.1	Speedometer located within direct field of view of legible both day and night?	the driver and clearly	y N N NA NA NA	
A.5.1.1	Speed values indicated in intervals not exceeding 2 highest value on the display is less than 200km/h), highest value is more than 200km/h). ? Please circ Graduations at least in 1, 2, 5 or 10km/h increment	or 30km/h (when the cle.	Y	
ADR 21/0	0 – INSTRUMENT PANEL			
CLAUSE NO	FEATURE		COMPLIANCE	NCI NO
21.2.1	Panel left of steering wheel appears to be padded?		y	
21.3.1	Interior compartment door latches operate?		y 🗆 n 🗆 na 🗆	
ADR 22/0	0 – HEAD RESTRAINTS			
CLAUSE NO	FEATURE		COMPLIANCE	NCI NO
22.2.1	Head restraints fitted to front outboard seats?		y \square N \square NA \square	
22.2.2.1	Distance between upper and lower edges not less than 115 mm?	mm	y N N NA NA	
22.2.2.2	Minimum height of upper boundary above intersection of seat cushion and seat back at centre line of seat > 700mm?.	mm	y	
22.2.3	Width not less than 170 mm for individual seat and 250 mm for bench seat at approx 700mm?	mm	у 🗆 n 🗆 na 🗆	
Notes:				

......

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

CLAUSE NO		FEATURE		COMPLIANCE	NCI NO
22.6	IF 'E' MARKED,	R25 OR R17 APPROVAL NO		#	
IF HEAD R	ESTRAINT NO	N-SOLID, GIVE DIMENSIO	ONS		
		A = B = C =	B A	A = B =	-

ADR 23/00 & 23/01 - PASSENGER CAR TYRES

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
23.2.3	For one tyre fitted, identify: (If tyre size different front and rear, complete for 1 Fr & 1 Rr tyre) (1) Manufacturer or trade markFr	#	
23.2.2.1.2	At least 4 tread wear indicators?	y 🗆 n 🗆 na 🗆	
23.2.3	Each tyre labelled on both sides, except for 'Asymmetrical' Tyres' which are at least labelled on the outer 'Sidewalls'?	y	
23.2.3.8	If tyre is 'Asymmetrical', outer face indicated?	y N NA NA NA	

Notes:		

VEHICLE INSPECTION REPORT

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
23.4	Regulation and marks DOT If `E' marked R30, Approval No	#	
ADR 25/00	- 25/02 - ANTI-THEFT LOCK		
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
25/01, 25.2.3* 25/02, A.5.9.1	Switch position 'Engine On' to 'Anti-theft' through 'Engine Off'?	Y	
25/01, 25.2.4 25/02, A.6.1,5	Key removal only in the anti-theft position?	y	
25/01, 25.2.5 25/02, A.6.1, A.6.3	With key in anti-theft position, is one of the following impossible? Steer vehicle/Engage forward drive gears/Release a brake? (Circle which is applicable)	Y	
25/01, 25.2.6.1 25/02, A.6.1.5	'Engine off' position to 'anti-theft' position by more than a single rotary or linear motion of the key, or if key removal activates the 'anti-theft device, more than 2mm of movement required to activate.?	Y	
25/01, 25.4 25/02, 6.0	If 'E' marked, R18 Approval No	#	
ADR 28/01	- EXTERNAL NOISE OF MOTOR VEHICLES		I
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
28.2.2.2	'Vehicle does not sound unduly noisy?	Y N N NA	
28.3	Exhaust system is original and in good condition with no leaks or corrosion?	y 🗆 n 🗆 na 🗆	
28.3	If 'E' marked, R51 Approval No	#	
Notes:			

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

ADR 29/00 - SIDE DOOR STRENGTH

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
29.1	Side intrusion bars fitted?	y	
ADR 30/00	and 30/01- SMOKE EMISSION CONTROL FOR DIESEL VEHICLES	5	
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
30/00, 30.2.3	ENGINE LABEL AND ITS LOCATION SATISFACTORY, AND MARKED WITH MONTH/YEAR OF MANUFACTURE ?	Y	
30/00, 30.5.1	REGULATION AND MARK (IF 'E' MARKED R 24, APPROVAL NO)	#	
30/01, 5.1.		"	
ADR 31/00	- PASSENGER CAR BRAKES (MA Category Only)		
Applicable of	only to existing Models until 1-Jan-2006.	1	1
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
31.2.1.1	Service brake, split system?	y N N NA NA	
31.2.1.3 31.2.2.3	Adequate provision made for adjustment of service and park brake systems?	Y	
31.2.5.1	(1) Combined reservoir for split system?(2) If yes, is there a divider fitted?	Y	
31.2.5.4	Labelling satisfactory and located on or near brake fluid reservoir cap?	Y N N NA	
31.2.3.1	Service brake failure indicator lamp: (1) Fitted?	Y N NA NA	
31.2.3.3	(2) Activation check satisfactory?	Y N N NA	
31.2.3.4.1	(3) Labelling satisfactory with at least the word 'BRAKE,' or ISO sym ?	Y N N NA	
31.2.3.4.3	Anti-lock system failure lamp (If fitted & used exclusively for Anti-lock System): (1) Activation check satisfactory? (2) Labelling satisfactory with the word 'Anti-lock' or equivalent? (3) Lens or lettering, Red or Yellow?	y □ N □ NA □	
31.2.2.1	Park brake mechanical only?	y \square N \square NA \square	
31.2.1.2 31.2.2.2	Braking controls readily accessible to driver and easily operated?	Y N NA NA NA NA NA	
31.2.4.1	Park brake indicator a separate Lamp (S), or a combination unit (C) with service brake failure lamp? (Indicate S or C).		
Notes:			

A 6 4.1.1

6

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
	Labelling satisfactory with the word 'PARK BRAKE,' or ISO symbol (P), or (if combined with service brake?	Y N N NA N	
ADR 31/01	- PASSENGER CAR BRAKES MA Category. (Optional for MB an	d MC category.)	
(For all NE\	W Models from 1-Jan-2004, for ALL Vehicles from 1-Jan-2006)	<u>-</u>	1
CLAUSE NO	FEATURE	COMPLIANCE	SSR NO
A 5.1.2.1 A 5.1.2.2 A 5.1.2.3	Braking controls readily accessible to driver and easily operated?	y □ N □ NA □	
A 5.2.2.2	Service brake control separate from Park brake?	Y N N NA N	
A 5.2.2.5	Secondary brake system provided?	y 🗆 n 🗆 na 🗆	
A 5.2.2.7	 Is service brake a split system? Combined reservoir for split system? If Yes, is there a divider fitted? 	Y	
A 5.2.3 A 5.2.8.1 A 5.2.3	 Is a Service brake failure RED tell-tale lamp fitted? For electrical detected failures is a YELLOW failure lamp fitted? Is a Park brake indicator lamp fitted? Park brake indicator a separate Lamp (S), or a combination unit (C) with service brake failure lamp?(Indicate S or C). 	Y	
A 5.2.6	Service brake on all wheels?	Y	
A 5.2.11	Adequate provision made for adjustment of service and park brake system?	y 🗆 n 🗆 na 🗆	
A 5.2.11.2	Is it possible to easily check wear of service brake linings? If NO Is an acoustic or optical warning device provided?	Y	
A 5.2.12	For hydraulic braking systems are the filling ports of the fluid reservoirs readily assessable and fluid level easily checked? If NO Is a RED warning signal provided to draw attention to a low fluid level?	Y	
A 5.2.13	Is a label identifying the type of fluid (DOT 3/DOT 4/DOT 5), and the symbol (For Non-Petroleum base fluid), or	y □ n □ na □	

Notes:				
•••••	•••••	•••••	••••••	••••••

fitted within 100mm of fluid ports?

Petroleum based fluid)

If ABS fitted is a YELLOW warning signal provided? Regulation and Mark (If 'E' marked R 13, Approval No) Y N N NA

#

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

ADR 34/01- CHILD RESTRAINT ANCHORAGES & CHILD RESTRAINTS

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
34.2.1,34.31 34.3.2	Child Restraint Anchorages provided for each applicable rear seating position? Note positions provided with CRA's (Circle where applicable) 2 nd Row L C R 3 rd Row L C R	y □ N □ NA □	
34.2.1	Child Restraint Anchor Fitting installed in at least the centre rear position, unless centre lap sash belt fitted? (Not required when certified to ADR 5/02) If not fitted in centre position note where fitted. L R	y □ N □ NA □	
34.2.1.1.2	For positions where 'Anchor Fitting' is not provided, anchorage has 5/16 UNC thread?	y	
34.2.1.2.2	For positions where 'Anchor Fittings' are not provided and a non-standard bolt is required, is the Bolt and appropriate spacer provided in the glove box?	y	
34.5.1	Is each 'Child Restraint Anchorage' and 'Child Restraint Anchor Fitting' located within the vehicle in a part of the body structure which would not normally be moveable, or if moveable would not alter the tension in any 'Upper Anchorage Strap'?	y	
34.5.2	Is anchorage located within the shaded area in Fig 6? Or	Y N N NA	
34.5.4	Is the entire 'Interface Profile' of each 'Child Restraint Anchor Fitting' located within the shaded zone shown in Figures 9 -13? If No	y	
34.5.4.1 34.5.4.1.1	Is 'Interface Profile' equipped with a routing device that 1. Ensures that the 'Upper Anchorage Strap' functions as if the 'Interface Profile' were located within the shaded zone?	y 🗆 n 🗆 na 🗆	
34.5.4.1.2	2. Is at least 65mm behind the 'Torso Reference Line', in case of a non-rigid webbing-type routing device or a deployable routing device, or at least 100mm, in the case of a fixed rigid routing device?	y □ N □ NA □	
34.2.1.1.2 34.6,	Clearance provided around each 'Fitting' to allow latching and unlatching of 'Attaching Clip'	y □ N □ NA □	
34.2.2	Location information and instructions for use provided?	y	
34.4.1.3	Access provided without the removal of items, except for closure plugs?	y \square N \square NA \square	
Notes:			
			•••••

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

ADR 35/01- COMMERCIAL VEHICLE BRAKE SYSTEMS (MB & MC CATEGORY ONLY)

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
5.1.1	Service brake on all wheels?	Y N N NA	
5.1.4 5.3.3	Adequate provision made for adjustment of service and park brake system?	Y N NA NA NA NA NA	
5.5.1	Secondary brake system provided?	y N N NA NA	
5.6.1 5.6.1.2	If service brake is hydraulic, is it a split system? (1)Combined reservoir for split system? (2) If yes, is there a divider fitted?	Y	
5.6.4	Label on or near brake fluid reservoir cap?	Y N N NA N	
5.2.1 5.2.6 5.2.10	Service brake failure indicator: (1) Provided? (2) Lamp activation satisfactory? (3) Labelling satisfactory with at least the word 'BRAKE', or ISO symbol	Y	
5.1.11	Audible indicator provided with single brake power unit?	Y N N NA N	
5.7.5.1	For system with brake power units, is a separate gauge provided for each reservoir?	y 🗆 n 🗆 na 🗖	
5.5.4	Braking controls readily accessible to driver and easily operated?	y N N NA NA	
5.3.1,5.3.2,	Park Brake. (1) Retention in applied position mechanical? (2) Control separate from service brake? (3) Min of 2 separate and distinct movements to release? If NO is it, Designed to minimise the possibility of inadvertent release?	Y	
35.2.2.31	(1)Park brake indicator a separate lamp (S), or a combined unit (C) with service brake failure lamp? (indicate S or C) (2) Labelling satisfactory with the word 'PARK BRAKE', 'PARKING BRAKE', or Or ?	Y	
35.7	If 'E' marked, R13 Approval No	#	
Notes:			

......

VEHICLE INSPECTION REPORT

ADR 36/00	- EXHAUST EMISSION CONTROL FOR HEAVY DUTY VEHICLES		
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
36.2.2.1	FOR VEHICLE CATEGORIES MB2 & MC2 ONLY(Over 2.7t GVM) Satisfactory label fitted to engine?	Y	
36.2.2.2 36.2.2.3	Label approved by the Environmental Protection Agency (USA) attached to the engine?	Y N N NA	
36.2.2.5 36.2.3.1	U.S. EPA or California Air Resources Board Approval No	#	
	Written maintenance instructions provided?	y \square N \square NA \square	
ADR 37/00 79/00 or 79	& 37/01- EMISSION CONTROL FOR LIGHT VEHICLES (NA to vel 9/01)	nicles certified to AD	R
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
37/00,37.3.6	FOR VEHICLE CATEGORIES MA, MB1 & MC1 ONLY (Under 2.7t GVM) Readily visible unleaded fuel label affixed near petrol filler inlet(s)?	Y N N NA	
37/00,37.3.7	Filler neck internal diameter more than 21.30 mm and less than 23.6 mm (for unleaded petrol nozzle only)	y 🗆 n 🗆 na 🗆	
37/00,37.3.5 .2	Satisfactory label fitted in engine compartment?	Y N N NA	
37/00,37.3.7	Filler neck will not allow the entry of leaded petrol nozzle?	y 🗆 n 🗆 na 🗆	
37/00,37.3.5 .2	Satisfactory label fitted in engine compartment (including RON if engine required to operate on 95/96 RON)?,	y	
37/00,37.3.8	Access prevented to idle air/fuel mixture screw?	Y N N NA N	
37/00,37.9	U.S. EPA Approval No	#	
37/00,37.3.5 .1	Written maintenance instructions provided?	y 🔲 N 🗎 NA 🔲	
ADR 42/04	- GENERAL SAFETY REQUIREMENTS		
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
5.	BONNET LATCHING If bonnet front opening, is a second latching position provided?	y	
6.	DIESEL ENGINES Is device fitted to prevent inadvertent starting of engine?	y	
7.1.1	STEERING SYSTEM Steering wheel located centrally or to the right?	Y N N NA	
Notes:			

VIR-1 VEHICLE INSPECTION REPORT

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
7.1.2	Are components essential to steering designed to transmit energy by mechanical means only?	y	
7.2	AUTOMATIC TRANSMISSION Fitted with automatic transmission ? If YES:	y	
7.2.1	Starter inoperative in forward or reverse?	y \square N \square NA \square	
9.1.1	ELECTRICAL WIRING Supported at not more than 600 mm intervals?	у 🗆 n 🗆 na 🗆	
9.1.2/3/4	Properly insulated, located and protected from chafing?	y \square N \square NA \square	
10.1.1	EXHAUST OUTLETS(1) Exhaust pipe extends at least 40 mm beyond rearmost unsealed joint of floor-pan?(2) Exhaust outlet within vehicle perimeter in plan?	Y	
10.2.1	If exhaust discharges to the side of vehicle is it to the right side and downwards between 15 deg and 45 deg to the horizontal?	y 🔲 n 🗎 na 🔲	
10.1.3	If the exhaust discharges to the rear of the vehicle, is it between 10 deg above and 45 deg below horizontal?	y \square N \square NA \square	
11.1.3	EXTERNAL OR INTERNAL PROTRUSIONS Devoid of external or internal projections or sharp or pointed fittings?	y \square N \square NA \square	
11.1.4	Bumper bar ends turned back?	y \square N \square NA \square	
14.1.1	WHEEL GUARDS (MUDGUARDS) Are front and rear wheels shrouded by wheel guards that will:	y □ N □ NA □	
	(1) Direct downwards stones, mud, ice and snow as far as practicable?	y \square N \square NA \square	
	(2) Prevent direct contact in collision?	y \square N \square NA \square	
14.1.2.1.1	Provides cover at least as shown in Fig. 1 or 2 of ADR 42/00 as applicable? (Fig. 1 for category MA, Fig. 2 for MB and MC)?	y □ N □ NA □	
14.2.5	For MB and MC Category only If mud-flaps are required to meet requirements of clause 42.12.2.2: do mud-flaps reach a point not higher than 230 mm above the ground for vehicles other than off-road vehicles, and 300 mm for vehicles designed for off-road operation, and provides cover for Overall Tyre Width of all tyres?	y	
15.	BRAKE TUBING AND BRAKE HOSES All brake hoses and tubing fitted to prevent chafing, kinking or other mechanical damage? For any one brake hose, identify (1) Location?	y □ n □ na □ #	
15	All brake hoses in a good condition and not perished or damaged?	y \square N \square NA \square	
Notes:			

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
18	TELEVISION AND VISUAL DISPLAY UNITS Television receiver visual display monitor fitted? If YES:	Y N N NA	
18.1.1/2	Is obstruction of driver's vision or impediment to driver or passenger movement prevented?	y	
18.1.3	Is it unlikely to increase risk of occupant injury?	Y N N NA	
18.2	Is driver's visibility of images other than for driver's aid prevented?	y \square N \square NA \square	
19.1	WINDOWS AND VENTILATION (1) Can at least half of the windows be opened? If NO:	y 🗆 n 🗆 na 🗆	
19.1	(2) Is alternative ventilation adequate?	y \square N \square NA \square	
19.3.2.1	Power for power windows available only through use of key? Except	y	
19.3.2.1.1.3	When the key has been removed do the windows remain operational for not more than 45 seconds?:	y	
19.3.2.1.1.4.2	If the driver's door is operated within the 45 second period, do windows remain operational for not more than 45 seconds OR	y \square N \square NA \square	
19.3.2.6	If power windows continue to operate with the key removed is an automatic reverse function incorporated?	y	
19.3.2.2	Are all the switches for the rear windows in close proximity of the driver?	y \square N \square NA \square	
19.3.2.2.1	If no, is there design features to enable the driver to turn off the rear window switches and to initiate the opening of the rear windows?	y	
19.3.2.4	For windows other than for the driver's position provided with momentary type switches or valves?	y □ N □ NA □	
21.2	WARNING DEVICE AUDIBLE Fitted with at least one horn with constant amplitude and frequency characteristics?	y	
23	DEMISTING OF WINDSCREENS Is a device fitted to remove condensed moisture from the windscreen?	y	
24	 WINDSCREEN WIPERS AND WASHERS (1) Is a power driven windscreen wiping system fitted? (2) Is a windscreen washing system, which directs water onto the swept area fitted? (3) Is the device/s for operating the wipers and washers within easy reach of the driver? 	Y	
Notes:			

......

VIR-1 VEHICLE INSPECTION REPORT

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
	TYRE AND RIM SELECTION Are NEW tyres fitted? For LIGHT TRUCK or TRUCK TYRES has ADR 23/- clause 23.2.3 and 23.4	Y	
	details been completed? Is a tyre placard fitted?	y	
25	Does the placard contains the following information:		
25	(1) Manufacturers recommended tyre size?	y \square N \square NA \square	
	(2) Recommended cold inflation pressures in Kpa?	Y N N NA	
	(3) Recommended load rating and speed category?	y O N O NA O	
	Maximum load rating and speed category of tyre fitted equal to or greater than that on the placard?		
		y O N O NA O	
	Are tyres on the vehicle included on the tyre placard and on the VIC?	y	
_	Part number if shown on the placard? Pt No	#	
ADR 44/02 -	SPECIFIC PURPOSE VEHICLE REQUIREMENTS	_	
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
	L.P.G. FUELLED VEHICLES		
44.6.3	Vehicle clearly permanently marked in a conspicuous position within the engine compartment with the following information?	Y N NA NA NA	
	(1) Installed as per AS1425-1989?	y 🔲 n 🔲 na 🔲	
44.6.3.1	(2) Identification of the installer? (If not the same as the manufacture,		
44.6.3.2	note details).	y \square N \square NA \square	
44.6.3.3			
44.5.4	(3) Date of installation?	y	
44.6.4	Are labels to be affixed to registration plates and supplied for inspection, at least 25 mm square and red in colour?	Y N N NA	
ADR 60/00 -	CENTRE HIGH MOUNTED STOP LAMPS		
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
60.4.1	Is a Central High mounted Stop Lamp fitted?	y N NA	
60.2.4.2	Does the lamp design provide for easy replacement of the	y \square N \square NA \square	
60.2.4.3	globe without the use of special tools?	Y LI N LI NA LI	
60.4.4.1	Mounted on the vehicles median longitudinal plane?	y \square N \square NA \square	
	Mounted with no part of the lens lower than the bottom		
60.4.4.2	edge of the rear window by more than 152 mm for	y \square N \square NA \square	
	convertibles, and 77 mm for other vehicles?		
Notes:			

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

ADR 61/02 - VEHICLE MARKING

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
	VEHICLE IDENTIFICATION NUMBER Is the VIN clearly visible on an integral part of the vehicle not easily removed?	Y	
5.1	If VIN is directly marked on an integral part of the vehicle, is the minimum height at least 7 mm? If NO What is height of VIN? Indicate in MM	Y	
	If VIN is on a separate plate which in turn is permanently affixed to an integral part of the vehicle, is the minimum height at least 4 mm?	y □ n □ na □	
7 7.1	Is the engine number permanently stamped, cast, laser engraved or combination of these on the main component of the engine?	y	
7.1.1	Can a legible engine number be seen when the engine is installed in the vehicle? If 'No' is one of the following met?	y	
7.1.2	Are only simple hand tools required to remove any vehicle components?	Y N N NA	
7.1.3	Or 2. Is a supplementary label placed in a conspicuous position in the engine compartment?	Y	
	Is the label adequately durable for its environment, and not removable other than by its destruction?	Y N N NA	
	Is the engine number satisfactorily located as per typical number on VIC form?	Y N N NA	
9.1	REGISTRATION PLATES		
9.1.1.1	Are all parts of the front and rear number plate made as	y \square N \square NA \square	
9.1.1.2	per Fig. 1 of the ADR below 1,300 mm from the ground?		
9.1.1.3	No part of the front and rear number plate obscured by any part of or equipment on the vehicle?	y N NA NA NA	
9.1.1.2	Rear number plate opening at least 372mm wide? If 'NO' is opening greater than 320mm wide? (Indicate widthmm)	Y N N NA	

Notes:		

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

62/01 - MECHANICAL CONNECTIONS P

ADR 62/01	– MECHANICAL CONNECTIONS BETWEEN VEHICLES		
CLAUSE NO	FEATURE	COMPLIANCE	SSR NO
10.1	COUPLINGS AND TOWBARS (OPTIONAL) (1) If fitted, does the ball of a ball coupling, for use with a trailer of	Y	
	ATM not exceeding 3.5t, have a diameter of 50mm?	y \square \square \square \square \square	
	(2) Is coupling marked '50' in 5mm high characters?	YUNUNAU	
13.2.1	If fitted, does the 'Towbar' display the following information when fitted to the vehicle;		
13.2.1	(1) The 'Towbar' manufacturer's name or trade mark?		
13.2.1.1 13.2.1.2	(2) The 'make and model' shown on the 'Compliance Plate' fitted to the vehicle for which it is designed, or manufacturer's part number?	Y	
13.2.1.2	(3) Its maximum rated capacity expressed in numerals not less than	y \square N \square NA \square	
13.2.1.3	6mm ?		
	Where the information above is not visible when the 'Towbar' is fitted		
	to the vehicle, is an additional plate showing the maximum rated	y \square \square \square \square	
13.2.2	capacity of the 'Towbar' fitted in a conspicuous position adjacent to the 'Towbar'?		
13.4.3	Safety chain attachments fixed to a part of the 'Towbar' which is permanently attached to the vehicle?	y	
ADR 69/00	- FULL FRONTAL IMPACT OCCUPANT PROTECTION (MA from	1-Jan-96, MB/MC fro	om
1Jan-00)			
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
	Seatbelt Warning System Visual Indicator;		
	(1) fitted?	y \square N \square NA \square	
5.5.1	(2) Activation check satisfactory?	·	
5.5.2	(3) Labelling satisfactory?		- .
	– OFFSET FRONTAL IMPACT OCCUPANT PROTECTION (MA w	ith Gvivi less than 2.	5τ
only)			
(MA only fr	om 1-Jan-00 for new models, 1-Jan-04 for all MA vehicles.)		
CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
6.1.1	Steering wheel has the inscription 'AIRBAG or SRS'?	y \square N \square NA \square	
6.1.2	If passenger's airbag fitted, is a Warning label as per pictogram figure1	Y N N NA	
	or 2 below fitted?		
	or 2 below fitted?		
	or 2 below fitted?	l	
	or 2 below fitted?		
Notes:	or 2 below fitted?		
Notes:			

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
	For Figure 1. (1) Warning label durably affixed such that it is visible to a person installing a rearward facing child restraint?	Y	
6.2.2	(2)If warning label is not visible when door is closed, is a permanent reference (AIRBAG or SRS AIRBAG) visible at all times? OR	y	
6.2.3	For Figure 2. Is the label durably affixed to each face of the passengers sun visor so that it is visible at all times, or is the warning visible on the face of the stowed sun visor and a second warning on the roof behind the sun visor?	y	
6.2.3	For Figure 1. Copy of warning label and detailed information (including the following text) "Extreme Hazard! Do not use a rearward facing child restraint on a seat protected by an airbag in front of it", in owners handbook?	Y	
6.2.4	For Figure 2. Copy of warning label and detailed information (including the following text) "Do not use a rearward facing child restraint on a seat protected by an airbag in front of it", in owners handbook?	Y	
2.4	If 'E' marked R94, Approval No.	#	
	DO NOT place rearseat on this seat will DEATH OR SERIOU	facing child th airbag	•



Dia Min 50 mm

Figure 2 Min 120 x 60 mm

Notes:	

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

ADR 79/00 – EMISSION CONTROLS FOR LIGHT VEHICLES MA MB & MC GVM less than 3.5t only.

(For existing Models only until 1-Jan-2006)

CLAUSE NO	FEATURE	COMPLIANCE	SSR NO
5.1.2.1 5.1.2.2.2	INLET ORIFICES FOR PETROL TANKS. Filler neck internal diameter not more than 23.6mm?(for unleaded fuel nozzle only) If filler neck is greater than 23.6mm, is an unleaded fuel symbol affixed near petrol filler inlet(s)?	Y	
7.1	If 'E' marked R83, Approval No.	#	

ADR 79/01 - EMISSION CONTROLS FOR LIGHT VEHICLES MA MB & MC GVM less than 3.5t only

(NEW Models from 1-JAN-2005, ALL Vehicles from 1-JAN-2006, Petrol LPG & NG only)

			SSR
CLAUSE NO	FEATURE	COMPLIANCE	NO
	INLET ORIFICES FOR PETROL TANKS.		
5.1.2.1	Filler neck internal diameter not more than 23.6mm?(for unleaded fuel nozzle only)	Y	
5.1.2.2.2	If filler neck is greater than 23.6mm, is an unleaded fuel symbol affixed near petrol filler inlet(s)?	Y LI N LI NA LI	
5.1.3	Is provision made to prevent excess evaporative emissions fuel spillage caused by a missing filler cap by one of the following;		
	(1) An automatic opening and closing, non-removable fuel filler cap?	y \square N \square NA \square	
	(2) Design feature which avoids excessive evaporative emissions in case of a missing fuel filler cap?	y	
	(3) Any other feature e.g. a tethered filler cap, a chained filler cap, or a locking filler using the ignition key. In the case of a key is the key only removable in the locked position?	y 🗆 n 🗆 na 🗆	
	If 'E' marked, R83 Approval No	#	

ADR 82/00 - ENGINE IMMOBILISER (From 1-Jul-01)

CLAUSE NO	FEATURE	COMPLIANCE	NCI NO
82.32.4.1	Is the Immobiliser set without supplementary action by the driver?	Y N N NA	
82.32.4	Is unsetting achieved by one of the following devices: mechanical key / key pad / remote control?	y	
82.32.6	Status Display if provided by Direction Indicators, do they Flash for not more than 3 seconds?	y N N NA	

Notes:	 	

VEHICLE INSPECTION REPORT

FOR USED VEHICLES OF CATEGORY MA, MB AND MC

CIRCULAR 0-4-12 CAMPERVANS AND MOTORHOMES

7	DESIGNATED SEATING POSITIONS.		
7.1	Is the number of 'Designated Seating Positions' equal to, or greater than the number of sleeping-berths provided?	y \square N \square NA \square	
	SEATS, SEATBELTS and SEATBELT ANCHORAGES.		
	Is there a prominently displayed durable label with the words 'THIS VEHICLE IS DESIGNED FOR THE CARRIAGE OFPERSONS' permanently	Y N N NA	
8	affixed to the interior of the motorhome? Are all the letters at least 6mm high?	y \square N \square NA \square	
8.1	Does the label include the following words "WARNING- THE SEATING POSITION(S) SHOWN BY 'X' ON THIS LABEL MUST NOT BE OCCUPIED WHILE THE VEHICLE IS IN MOTION"?	Y	
	Is a facsimile of the label provided in the Owner's manual?	Y	
8.2	Are all seat anchorages, seatbelts, seatbelt anchorages and child restraint anchorages added or modified by the conversion in designated seating positions in accordance with ADR 3/xx, ADR 4/xx and ADR 5/xx?	Y	
	If any swivelling seat is used as a designated seating position in any of its positions, is it capable of being locked in each of those positions and provided with ADR complying seat, seat anchorages, seatbelt assemblies and seatbelt anchorages? If any swivelling seat is able to be locked in a position other than as	y □ N □ NA □	
8.2	certified as a 'Designated Seating Position' is a durable and permanent label provided in a visible position adjacent to the seat, in 6MM high letters as follows:	y 🗆 n 🗆 na 🗖	
	WARNING: THIS SEAT IS ONLY TO BE USED IN THE (FORWARD/REARWARD/etc* - as appropriate) FACING POSITION WHILE THE VEHICLE IS IN MOTION.	y □ n □ na □	
	Is a facsimile of the label provided in the Owner's manual?		
8.3	For seats other than 'Designated Seating Positions' are no seatbelts, child restraint anchorages or any other equipment that may imply they are for use in transport?	Y N N NA	
8.4	If CRA's are fitted, do they meet the requirements of the motorhome vehicle category?	Y N N NA	
9	GLAZING MATERIAL		
9.1	Are all vehicle windows and any glazing material that is within the head impact area marked in accordance with ADR 8/xx?	Y N N NA	
10	LIQUEFIED PETROLEUM GAS (LPG)	y \square N \square NA \square	
10.1	Has installation of LPG appliances been conducted by a licensed gas fitter?		
Notes:			
•••••			

VEHICLE INSPECTION REPORT

	GENERAL SAFETY		
11 11.2	If the electrical installations are intended for connection to a power system other than the vehicle's, has it been installed by a licensed electrician?	Y N N NA	
11.3	In addition to the tyre placard requirements of ADR 42/04 does the tyre placard (or an additional supplementary placard) display the <i>Gross Axle Load Rating</i> (GALR) of each <i>Axle</i> or <i>Axle Group</i> ?	y	
12.1.3	Does the VIC include in 'remarks' the individual axle group loads for each variant?	y	
ADR 44/02	FIRE EXTINGUISHERS.		
44.8.3	For single compartments at least one extinguisher (class 1A: 5B) suitably located and supported by a suitable bracket?	Y N N NA	
	For multi-compartment vehicles at least two extinguishers, (class 1A : 5B) suitably located and supported by a suitable bracket?	y N NA NA	
FOR LEFT TO	RIGHT HAND DRIVE CONVERSIONS		
Has vehicle k and evidence	peen converted from left hand to right hand drive in accordance with VSB 4 e?	Y N NA NA NA	
	Has the Vehicle Inspection Certificate (VIC) been checked and found satisfactory?	Y	
	Has the Initial Inspection Report been checked and found satisfactory	y 🗆 N 🗆	
Has the Consumer Information Notice been checked and found satisfactory?		Y	
	Has the Completed Vehicle Inspection Report been checked and found satisfactory?	Y	
Inspectors;			
Name: Date:			
Name:	Signature: Date:		
Notes:			